

# Product Data Sheet

## dekopin

### Writable Magnetic Boards

# dekodur®



## Product Description

The dekopin product group is a magnetic decorative high-pressure laminate (HPL) for use in interior design and meets the requirements of the normative „**Specifications for laminates with alternative core structure**“ laid down in **DIN EN 438/1-9**. All plain, wood, stone and fantasy decors in the Dekodur collection as well as some selected aluminium decors, mainly from the category of scratch-resistant aluminium surfaces, can be selected as surfaces. Please note our current price list. Custom-made digital print surfaces are also available on request and from a minimum quantity of 30 panels. DEKODUR uses a metal middle layer to achieve a high magnetic adhesion. By using power magnets, this holding force can be improved considerably. The fire behavior of the dekopin standard quality corresponds with DIN EN 13501-1, fire class „D-s2,d0“, on request it can be produced with fire class B-s2,d0.

**Note:** Fire test performance will depend on the Standard required by the application field EN 13501-1, on the laminate thickness, type and thickness of the substrate and adhesive used. The fire classification of the composite panel is under the responsibility of the manufacturer of the final composite. On request, we are supply ready-made standard MDF composite panels and A2-s1-d0 composite panels.

### Backing Material\*

With reference to the DIN EN 14323 standard, a guarantee that composite elements and direct coatings will not warp can only be granted if the elements are laminated with the same material on front- and backside (surface, thickness and embossing).

### Magnetic HPL




MH/A 341/SR



MH/A 350/SR



MH/A 356/SR



MH/E6

HGL/MAT\*/AGT\*\*/  
MPM/SMT



MH/E11

HGL/MAT\*/AGT\*\*/  
MPM/SMT



MH/E110

HGL/MAT\*/AGT\*\*/  
MPM/SMT

**\*MAT = Silk matt surface**  
especially for liquid chalk

**\*\*AGT = Anti Ghosting**  
Matt surface

- can be written on with board markers and wiped dry without residue
- ideal as a projection surface (beamer friendly).
- leaves no fingerprints

**\*\*\*FUS (Fusion) Surface** (especially for school chalk and liquid chalk)

- supermatt
- antifingerprint
- abrasion resistant (class 3)

# dekodur®

### dekopin Properties:



**Lightfast**



**Abrasion resistant**



**Food safe**



**Resistant to cleaning**



**Graffiti resistant**



**Magnetic**



**Flame retardant**  
upon request




**A2 non-combustible**  
upon request (composite board)

• Basically we always recommend the symmetrical construction. If, at the customer's request, a non-symmetrical structure is required, the responsibility for a later possible delay due to the non-symmetrical structure of the composite element lies with the customer himself. The recommended support plate thickness is  $\geq 18\text{mm}$ . Counter balancing Material upon request.

## Delivery form and quality

All dekopin magnetic boards are offered in the dimensions 2440 x 1220 mm and 3050 x 1220 mm and are supplied with a protective foil.



## Applications and processing methods

The processing of dekopin magnetic boards into composite elements is influenced by the use of a wide variety of processing methods and adhesive systems. Please contact your adhesive manufacturer before processing. A general indication of the processing temperature of dekopin laminates is a thermal value range of up to 50°C. The dwell time of the pressed material in the press depends on the adhesive system used. Due to the central metal layer, flying sparks can occur during processing. Appropriate precautions and precautionary measures are therefore essential. dekopin magnetic boards can be sawed, milled and drilled with carbide-tipped tools. Many HM circular saw blades are suitable if the number of teeth is correspondingly high and the tooth shape trapezoid/flat/trapezoid (Leuco format circular saw blade HW „TR-F“ with cutting material: special HW grade HL Steel 17) is used. When cutting the panels to size, care must be taken to ensure that the material to be cut is well flat. If necessary, an additional support should be used when cutting to size to prevent tearing.

## Inscribing, Cleaning and Care

Before the first use, after removing the transport protective film, a basic cleaning is absolutely necessary to remove any adhesive residues of the protective film! Commercially available glass cleaner is suitable for this purpose, which is removed with a soft, coarse-fibred microfibre cloth (do not use greasy cleaning agents such as dishwashing detergent or soap suds).

**We recommend the use of the following board markers:**

<b>Edding</b>	Whiteboard-Marker 360 or 363
<b>Staedler</b>	Whiteboard Marker Lomocolor 351/3
<b>PK</b>	Super Chalks Liquid chalk from ILLUMIGRAPH
	Liquid chalk from ZIG.
<b>ZIG</b>	Liquid chalk from

The surface with the designation AGT (anti-ghosting) is suitable for marking with chalk and board markers as well as a projection surface.

**Depending on the pen and surface, different cleaning methods and agents are required:**

Struktur	Boardmarker	Liquid Chalk	Schoolchalk
HGL	dr	wt	–
MAT	–	wt	–
MPM	–	wt	dr
AGT	dr	wt	dr
FUS	–	wt	dr

dr = Dry cleaning with microfibre cloth or melaminE sponge/dirt eraser  
wt = Wet cleaning with glass cleaner (Regular, wet basic cleaning also improves the properties of dry cleaning).

### Cleaning of Surfaces with Liquid Chalk\*

ZIG	Illumigraph	white	dr
ZIG	Illumigraph	red	dr
ZIG	Postermann	black	wt
Sigel	Chalkmarker 50	white	dr
Uni	Chalk Marker	silver	wt
Edding 725	Neon Board Marker	white	dr

Experience shows that quality, age, duration of use and storage of the pens have a significant influence on the cleaning result. Only when the pens are stored horizontally the mixing ratio of the Boardmarker ink (3-components) required for dry wiping can be guaranteed. It is therefore essential to observe the manufacturer's storage instructions.



Liquid crayons with a higher or coarser lime content can lead to surface damage.

## Note and cleaning instructions:

Since HPL surfaces, especially with a matt finish, have a higher porosity than, for example, a high-gloss finish, the surface AGT should be used if dry cleaning of the dekopin magnetic boards is desired. When using liquid chalk, wet cleaning is absolutely necessary. For marking with liquid chalk we recommend the use of our surface MAT.

However, a residue-free cleaning of dekopin magnetic boards cannot be guaranteed, since we have no influence on the quality, age and storage of the pens used. We recommend to test different pens before use or to perform a basic cleaning from time to time.

For basic cleaning of dekopin magnetic panels, standard glass cleaners or the cleaning agent Hraniclean 01 from Hranipex in combination with the Power Clean dirt eraser from Sito or the Express dirt eraser from Mr. Clean have proven to be effective.

## Storage

The dekopin boards must preferably be stored in a closed room **at 18 - 25°C and 50 - 60%** relative humidity over the entire surface and horizontally **with a distance of 200 mm from the floor**. They should be weighted down with a cover plate and not be exposed to direct sunlight or draughts. When storing in a cold environment, it is essential that the boards are **acclimated to room temperature for at least 24 hours before gluing!** If this is not observed, cracks may occur in the surface of the magnetic boards.

The dekopin boards must be stored horizontally and must not be lifted individually. To avoid kinks in the metal center layer, the boards should only be moved horizontally and in pairs.

### The board stacks must

- be protected from moisture and condensation water
- not be exposed to direct sunlight
- not be placed in a hot air stream
- must not be exposed to heat > 50°C
- must not be exposed to direct heat radiation



If horizontal storage is not possible, an inclination of approx. 80° with full-surface support and lower counter bearing is recommended. Products must be stored packed.

## Disposal

The processing residues of our dekopin magnetic boards are waste residues according to the TA - Abfall, version of 28.3.91, category I, no. 571 and are classified as „other hardened plastic waste“. This waste can be incinerated without hesitation in officially approved industrial combustion plants or disposed of in accordance with local waste regulations.

# How to Clean Your Magnetic HPL

## Basic Cleaning

Our Magnetic HPL is coated with a transport protective film. Before using, peel off the film and remove any surface residues with or ethyl alcohol. The V100 thinner from Edding works just as well.

## Regular Cleaning

All surfaces that can be written on can simply be wiped clean with a microfiber cloth or melamine sponge.

Make sure the ink has dried before wiping it off. This helps to avoid „ghosting“.

Microfiber-cloths and melamine sponges are available in most super-markets.

## Regular Basic Cleaning

From time to time, we recommend a thorough basic cleaning of the magnetic HPL with ethylene alcohol, spirit or the thinner V100 from Edding. This will keep the surface clear of residues.

Since the magnetic HPL can also be used as a projection surface for projectors, regular thorough cleaning is also recommended.

## Important note

### Avoid

- soap-containing nano-based cleaning agents. These contain oil-based, lipid-replenishing substances that make subsequent use and cleaning more difficult.
- rubbing or scratching with hard objects such as brushes etc. They create damages to the surface.
- sponges in general – with the exception of melamine sponges.

## Boardmarker

Our experience shows that the quality of the board markers has a considerable influence on the cleaning result. We received best results using non-permanent markers

### Edding 360 oder 363 Board Markers

**Tip:** Always store the pens horizontally and shake vigorously before use. Follow the manufacturer's instructions.

